

UNITED STATES PATENT AND TRADEMARK OFFICE
CERTIFICATE OF CORRECTION

PATENT NO. : 6,952,772 B2
APPLICATION NO. : 09/764536
DATED : October 4, 2005
INVENTOR(S) : Vinay Deo et al.

Page 1 of 4

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

On the Title page, in field (54), in "Title", in column 1, line 3, after "PROTOCOL"
insert -- , DEVICE, AND NETWORK INDEPENDENT FASHION --.

On the Title page, in field (56), under "Foreign Patent Documents", in column 2, line 8, delete
"97/124650" and insert -- 97/12460 --, therefor.

In column 1, line 3, after "PROTOCOL" insert -- , DEVICE, AND NETWORK INDEPENDENT
FASHION --.

In column 1, line 9, delete "above mentioned" and insert -- above-mentioned --, therefor.

In column 1, line 39, after "display" insert -- . --.

In column 2, line 35, delete "-radio" and insert -- radio --, therefor.


In column 5, line 3, delete "storms" and insert -- stored --, therefor.

In column 8, line 3, delete "6S" and insert -- 65 --, therefor.

In column 8, line 10-20, delete "Other input devices (not shown) may include a joystick,
game pad, satellite dish, scanner, or the like. These and other input devices are
often connected to the processing unit 48 through a serial port interface 76 that is
coupled to the system bus 52, but may be connected by other interfaces, such as a
sound card, a parallel port, game port or a universal serial bus (USB) A monitor 77 or
other type of display device is also connected to the system bus 52 via an interface,
such as a video adapter 78. In addition to the monitor 77, desktop computers may
typically include other peripheral output devices such as speaker 75 and printers."
and insert -- Other input devices (not shown) may include a joystick, game pad,
satellite dish, scanner, or the like. These and other input devices are often connected
to the processing unit 48 through a serial port interface 76 that is coupled to the system
bus 52, but may be connected by other interfaces, such as a sound card, a parallel

Signed and Sealed this

Third Day of August, 2010



David J. Kappos
Director of the United States Patent and Trademark Office

port, game port or a universal serial bus (USB). A monitor 77 or other type of display device is also connected to the system bus 52 via an interface, such as a video adapter 78. In addition to the monitor 77, desktop computers may typically include other peripheral output devices such as speaker 75 and printers. --, therefor on line 9 after “microphone 74.”.

In column 9, line 9, delete “method’s” and insert -- methods --, therefor.

In column 12, line 45, delete “Similarly” and insert -- similarly --, therefor.

In column 12, line 55, delete “draw” and insert -- data --, therefor.

In column 14, line(s) 25–28, delete “

Status	Key Index	Expiration Date	Address Tag	Address Info	Address Name	Description
(1)	(1)	(2)	(8)	(n)	(32) *	(64) *

insert --

Status	Key Index	Expiration Date	Address Tag	Address Info	Address Name	Description
(1)	(1)	(2)	(8)	(n)	(32) *	(64) *

--.

In column 14, line 45, after “processed)” insert -- . --.

In column 14, line 63, delete “ADDRESS_FLAG_PU_ONLY” and insert -- ADDRESS_FLAG_PO_ONLY --, therefor.

In column 14, line 64, delete “non-O” and insert -- non-0 --, therefor.

In column 15, line 1, delete “non-O” and insert -- non-0 --, therefor.

In column 16, line 10 (Table), delete “2” and insert -- 1 --, therefor.

In column 16, line 11 (Table), delete “Addr0Gp0” and insert -- Addr1Gp0 --, therefor.

In column 16, line 12 (Table), delete “Addr0Gp0” and insert -- Addr2Gp0 --, therefor.

In column 16, line 19 (Table), delete “Addr0GpN” and insert -- AddrNGpN --, therefor.

In column 16, line 45 (Table), delete “0x05” and insert -- 0x08 --, therefor.

In column 16, line 50 (Table), delete “GROUP_FLAG_PU_ONLY” and insert -- GROUP_FLAG_PO_ONLY --, therefor.

In column 16, line 52, delete “non-O” and insert -- non-0 --, therefor.

In column 16, line 55, delete “non-O” and insert -- non-0 --, therefor.

In column 16, line 64, delete “nave” and insert -- name --, therefor.

In column 17, line 28, delete “unsigned” and insert -- Unsigned --, therefor.

In column 17, line 62, after “present)” insert -- . --.

In column 18, line 3, delete “wstructSize” and insert -- wStructSize --, therefor.

In column 18, line 5, delete “compatibilty” and insert -- compatibility --, therefor.

In column 18, line 24 (Table), delete “Expirationdate” and insert -- ExpirationDate --, therefor.

In column 18, line 27 (Table), after “AddressTagLen =” delete “N₂” and insert -- N₁ --, therefor.

In column 18, line 51, delete “date-0if” and insert -- date. 0 if --, therefor.

In column 18, line 54, delete “KeysagLen” and insert -- KeyTagLen --, therefor.

In column 19, line 37, delete “dwMemberValidmask” and insert -- dwMemberValidMask --, therefor.

In column 19, line 41, delete “is” before “valid”. (second occurrence)

In column 19, line 45, delete “service” and insert -- Service --, therefor.

In column 19, line 59, delete “fox” and insert -- for --, therefor.

In column 20, line 14 (Table), delete “DwalgCode” and insert -- DwAlgCode --, therefor.

In column 20, line 33, delete “KeTag” and insert -- KeyTag --, therefor.

In column 20, line 36, after “encryption” delete “.”.

In column 20, line 49 (Table), delete “Operationcode” and insert -- OperationCode --, therefor.

In column 21, line 1, delete “RADIO_PGM_OPERATION PROGRAM” and insert -- RADIO_PGM_OPERATION_PROGRAM --, therefor.

In column 21, line 3, delete “RADIO_PGM_OPERATION UNPROGRAM” and insert -- RADIO_PGM_OPERATION_UNPROGRAM --, therefor.

In column 21, line 9, delete “RADIO PGM-TYPE-KEY” and insert -- RADIO_PGM_TYPE_KEY --, therefor.

In column 21, line 49 (Table), delete “GrouptagLen” and insert -- GroupTagLen --, therefor.

In column 21, line 61, delete “(RADIO_CRYPT” and insert -- (RADIO_CRYPT) --, therefor.

In column 22, line 9, delete “BYTE-AddressTagLen” and insert -- BYTE AddressTagLen --, therefor.

In column 22, line 42, delete “dwcode” and insert -- dwCode --, therefor.

In column 22, line 55, after “pBufOut” insert -- . --.

In column 25, line 15, delete “derail” and insert -- detail --, therefor.

In column 25, line 51, after “*pCryptInput” insert -- , --.

In column 25, line 52, after “*pbKeyValue” insert -- , --.

In column 26, line 36, delete “(DecryptedRadiopgm)” and insert -- (DecryptedRadioPgm) --, therefor.

In column 27, line 21, delete “Radio Pgm” and insert -- Radio_Pgm --, therefor.